

Product specifications for the Mobi Portable Room Divider Range

## **Frame & panel measurements**

Frame thickness - 11mm

Frame width (Top Bar) - 15mm / (Bottom Bar) - 47mm

Panel size - 687mm

Stability feet - 500 x 50 x 4mm

From bottom of panel to floor - 50mm

## **Materials**

Frame - Powder coated aluminium

Castor wheels - Polypropylene

Stability Feet - Steel

\*Stability feet are trip and wheelchair friendly with round edges

## **Fire Safety Elements**

Laminate

Tested to standard UNE EN 13501-1:07+A1:2010

Anti-bacterial

Garbe fabric collection has been tested and passed BS 5852 Crib 5 - EN1021 1+2

Flammability performance is dependent upon components used

Loop Nylon

Loop Nylon fabric has been tested to BS 5867-2 : Type B : 2008

Flammability performance is dependent upon components used

Plastic Components

Manufactured using non-flammable, self-extinguishing plastic.

Aluminium

Has a melting of 660°C and is not considered to be a fire hazard.

## **Panel Finish Information**

Easy Clean: HPL (high pressure laminate)

Anti-Bacterial: Garbe Fabric 88% PVC / 12% Poly/Cotton

Fabric: Brushed loop nylon

Printed: Gloss varnish finish

## Product Weights for Mobi Loop Nylon

### Box Size

Please note: box sizes & quantities vary based on order volume and panel size.

### Weights

Weight includes all framework, stability feet & packaging

1200mm High	1500mm High	1800mm High
2 way - 6.3kg	2 way - 7.25kg	2 way - 9.8kg
3 way - 8.3kg	3 way - 10.1kg	3 way - 14.3kg
4 way - 17.2kg	4 way - 15.4kg	4 way - 17.3kg
5 way - 14.3kg	5 way - 17.3kg	5 way - 18.5kg
6 way - 16.6kg	6 way - 21kg	6 way - 21.5kg
7 way - 18.1kg	7 way - 21.6kg	7 way - 25kg
8 way - 19.6kg	8 way - 23.6kg	8 way - 32kg
9 way - 22.1kg	9 way - 26.6kg	9 way - 35.6kg